



Cisco SPA 303 3-Line IP Phone

Basic and Affordable IP Phone for Business or Home Office



Highlights

- 3 line phone business-class IP phone
- Connects directly to an Internet telephone service provider
- Dual switched Ethernet ports, speakerphone, caller ID, call hold, conferencing, and more
- Easy installation and highly secure remote provisioning, as well as menu-based configuration
- Supports Session Initiation Protocol (SIP)

Telephony Features

- Three voice lines
- Pixel-based display: 128 x 64 monochrome graphical liquid crystal display (LCD)
- Line status: active line indication, name and number
- Menu-driven user interface
- Speakerphone
- Call hold
- Music on hold
- Call waiting
- Caller ID name and number
- Call transfer: attended and blind
- Three-way call conferencing
- Multiparty conferencing via external conference bridge
- Automatic redial of last calling and last called numbers
- On-hook dialing
- Call pickup: selective and group
- Call park and unpark
- Call forwarding: unconditional, no answer, and on busy
- Call logs (60 entries each): made, answered, and missed calls
- Redial from call logs
- Personal directory with auto-dial (100 entries)
- Do not disturb
- Digits dialed with number auto-completion
- Anonymous caller blocking
- On-hook default audio configuration (speakerphone and headset)
- Multiple ring tones with selectable ring tone per line
- Called number with directory name matching
- Ability to call number using name: directory matching or via caller ID
- Subsequent incoming calls show calling name and number
- Date and time with support for intelligent daylight savings
- Call duration and start time stored in call logs
- Call timer
- Speed dialing (8 entries)
- Intercom
- Group paging

Hardware Features

- Pixel-based display: 128 x 64 monochrome LCD graphical display with backlight
- Dedicated illuminated buttons for:
 - Audio mute on/off
 - Headset on/off
 - Speakerphone on/off
- 4-way rocking directional knob for menu navigation
- Voicemail message waiting indicator light
- Voicemail message retrieval button
- Dedicated hold button
- Settings button for access to feature, setup, and configuration menus
- Volume control rocking up/down knob controls handset, headset, speaker, ringer
- Standard 12-button dialing pad
- High-quality handset and cradle
- Built-in high-quality microphone and speaker
- Headset jack: 2.5 mm
- LED test function
- Two Ethernet ports with integrated Ethernet switch: 10/100BASE-T RJ-45
- 5 VDC universal (100–240V) switching included

Regulatory Compliance

- FCC (Part 15, Class B) , UL, CE Mark, A-Tick

Documentation

- Quick-Start Installation and Configuration Guide
- User Guide

Package Contents

- Cisco SPA 303 IP phone, handset, and stand
- Handset cord
- RJ-45 Ethernet cable
- Power adapter

Cisco SPA 303 3-Line IP Phone

POWER SUPPLY

- Switching type (100–240V) automatic
- DC input voltage: +5 VDC at 1.0A maximum

PHYSICAL INTERFACES

- Two 10/100BASE-T RJ-45 Ethernet ports (IEEE 802.3)
- Handset: RJ-9 connector
- Built-in speakerphone and microphone
- Headset 2.5-mm port

INDICATOR LIGHTS/LEDS

- Speakerphone on/off button with LED
- Headset on/off button with LED
- Mute button with LED
- Message waiting indicator LED
- LED test function

BODY DIMENSIONS

- 220 x 198 x 30 mm (8.66 x 7.80. x 1.18 in.) (W x H x D)

UNIT WEIGHT

- 1.50 lb (0.68kg)

OPERATING TEMPERATURE

- 0° – 40°C (32° – 104°F)

STORAGE TEMPERATURE

- -20° – 70°C (-13° – 185°F)

OPERATING HUMIDITY

- 5% to 95% noncondensing

STORAGE HUMIDITY

- 5% to 95% noncondensing